



REQUEST FOR QUOTATION NO.: 2023-10-074

Date: October 2, 2023

Procurement Title : One (1) Lot Supply, Delivery, Mounting, Connecting, and Programming of CCTV for the Commission on Filipinos Overseas

Purchase Request No. : 2023-08-126

Approved Budget for the Contract : Php 450,000.00 (Vat Inclusive)

Sir/Madam:

The Commission on Filipinos Overseas invites PhilGEPS registered suppliers to quote the latest market price of the item/s described/listed below. Quotations must be placed in **TWO (2) sealed envelopes**. The first envelope should contain the original documents while the second envelope (COPY 1) should contain copies of the documents. Please submit your sealed envelopes at the **2nd floor, Administrative and Finance Division, New Golden City Builders Building, 1388 Icasiano Street., corner Union Street, Paco, Manila** or you can send your files via email at bac.secretariat@cfo.gov.ph on or before **October 09, 2023; 10:00 A.M.**

DOCUMENTS SUBMITTED VIA EMAIL SHOULD BE PASSWORD-PROTECTED. PASSWORDS SHOULD BE GIVEN TO THE BAC SECRETARIAT ON THE OPENING DATE BY THE BIDDER'S REPRESENTATIVES ATTENDING VIA ZOOM.

I. General Terms and Condition:

1. Quotations should be addressed to the CFO Bids and Awards Committee and must be placed in **two (2) sealed envelopes**. The first envelope should contain the original documents while the second envelope should contain copies of the documents;
2. Price quotation/s must be valid for a period of thirty (30) calendar days from the date of submission;
3. Quotations should be **inclusive of all cost and applicable taxes**;
4. The following documents should be submitted **along with the sealed quotation or during bid/offer evaluation**:
 - PhilGEPS Registration Number/Certificate;
 - Mayor's/Business Permit;
 - BIR Form 2303 Certificate;
 - SEC or DTI Certificate;
 - Income/Business Tax Return;
 - Notarized Omnibus Sworn Statement;
 - Product Brochure;
 - Copy of any Valid ID of the Authorized Representative;
5. Bidders must have a Land Bank account for payment purposes. Otherwise, bank fees shall be for the account of the winning bidder.





COMPANY NAME : _____
 ADDRESS : _____
 PhilGEPS REGISTRATION No.: _____ VALID UNTIL: _____

ITEM DESCRIPTION	APPROVED BUDGET FOR THE CONTRACT (VAT INCLUSIVE)	QUOTATION/ BID AMOUNT (TOTAL COST) (VAT INCLUSIVE)
One (1) Lot Supply, Delivery, Mounting, Connecting, and Programming of CCTV for the Commission on Filipinos Overseas Inclusions: 2 units of 32 inches Digital Video Recorder with 16 ports POE 6 units 10TB Hard Disk Drives 24 units 4MP Fixed Dome IP Camera Colored 2 units 32 inches Monitor Accessories: HDMI Cables, Mouse, Bracket Warranty: 1 year on parts and 2 years warranty on support maintenance	PHP 450,000.00	

Delivery Schedule: 20 Calendar Days upon receipt of the Purchase Order

Technical Specifications: Please see ANNEX A

After careful evaluation of the General Terms and Conditions, Specifications, Inclusions, and Snacks I/WE hereby accept and submit our quotation based on the items and prices above.

The CFO reserves the right to accept or reject any bid, to annul the bidding process, and to reject all bids at any time prior to contract award, without thereby incurring any liability to the affected bidder or bidders.

 Signature over printed name (Owner/Authorized Representative)

Telephone/Mobile No.: _____
 Email Address : _____
 Date : _____

For Further information, please refer to:

KEESHIA MAE L. ACEDERA

Procurement Officer

Email: bac.secretariat@cfo.gov.ph

Tel. No: [8552-4792](tel:8552-4792)



TECHNICAL SPECIFICATION

32CH DIGITAL VIDEO RECORDER

IP video input - 32-ch
Up to 12 MP resolution
Incoming bandwidth : 256 Mbps
Outgoing bandwidth : 160 Mbps
HDMI output : 1-ch, 4K (3840 x 2160)/30 Hz, 2K (2560 x 1440)/60 Hz, 1920 x 1080/60 Hz, 1600 x 1200/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz, 1024 x 768/60Hz
VGA output : 1-ch, 1920 x 1080/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz, 1024 x 768/60Hz
Video output mode : HDMI/VGA independent output
CVBS output N/A
Audio output : 1-ch, RCA (Linear, 1 K Ω)
Two-way audio input : 1-ch, RCA (2.0 Vp-p, 1 K Ω , using the audio input)
Decoding
Decoding format : H.265/H.265+/H.264/H.264+
Recording resolution
12MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/
720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous playback : 8-ch 16-ch
Capability : 1-ch@12MP (30fps)/2-ch@8 MP (30 fps)/4-ch@4 MP (30 fps)/8-ch@1080p (30 fps)
Stream type : Video, Video & Audio
Audio compression : G.711ulaw/G.711alaw/G.722/G.726
Network
Remote connection 64-ch 128-ch
Network protocol
TCP/IP, DHCP, IPv4, Hik-Connect, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS
Network interface 1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
PoE
Interface
8, RJ-45 10/100 Mbps self-adaptive Ethernet interface
16, RJ-45 10/100 Mbps self-adaptive Ethernet interface
Power \leq 200 W
Supported standard IEEE 802.3 af/at
Auxiliary Interface
Serial interface 2 RS-485 (half-duplex), 1 RS-232
SATA 4 SATA interfaces
Capacity Up to 10 TB capacity for each disk
Alarm in/out¹ 16/4 16/4 (16/9 is optional)
USB interface Front panel: 2 x USB 2.0; Rear panel: 1 x USB 3.0
General
Power supply 100 to 240 VAC, 50 to 60Hz
Consumption (without HDD and PoE off)
 \leq 20 W (without enabling PoE and HDD)
Note:
1: Alarm in/out can be optional for certain models. If you select a device model with "/ALARM 16+9", the device will

TECHNICAL SPECIFICATION

	<p>have 16 alarm inputs and 9 alarm outputs. The 9th alarm supports control 12V.</p> <p>Dimension Working temperature -10 °C to 55 °C (14 °F to 131 °F) Working humidity 10% to 90% Dimension (W × D × H) 445 × 400 × 75 mm (17.5"× 15.7" × 3.0") Weight (without HDD) ≤ 5 kg (11lb.)</p> <p>Certification FCC Part 15 Subpart B, ANSI C63.4-2014 CE EN 55032: 2015, EN 61000-3-2, EN 61000-3-3, EN 50130-4, EN 55035: 2017 Working temperature -10 °C to 55 °C (14 °F to 131 °F) Working humidity 10% to 90% Dimension (W × D × H) 445 × 400 × 75 mm (17.5"× 15.7" × 3.0") Weight (without HDD) ≤ 5 kg (11lb.)</p> <p>Certification FCC Part 15 Subpart B, ANSI C63.4-2014 CE EN 55032: 2015, EN 61000-3-2, EN 61000-3-3, EN 50130-4, EN 55035: 2017</p>
16 ports POE	<p>Switcher type IP POE Yes Video Inputs/ ports 16 Channels Support IPv4/IPv6 and DHCP</p>
10TB Hard Drive	<p>Must be compatible to the NVR above</p>
4MP FIXED DOME IP Camera	<p>Image Sensor 1/3" progressive scan CMOS Min. Illumination Color: 0.01 Lux @(F2.0, AGC ON), B/W: 0 Lux with IR Shutter Speed 1/3 s to 1/100, 000 s Slow Shutter Yes Wide Dynamic Range 120 dB Day & Night IR cut filter Angle Adjustment Pan: 0° to 355°, tilt: 0° to 75°</p> <p>Lens Focal Length & FOV 2.8 mm, horizontal FOV 98.0°, vertical FOV 53.1°, diagonal FOV 114.7° 4 mm, horizontal FOV 78.7°, vertical FOV 43.1°, diagonal FOV 92.3°</p> <p>Lens Mount M12 Focus Fixed Aperture F2.0 Illuminator IR Wavelength 850 nm IR Range Up to 30 m</p> <p>Video Max. Resolution 2560 × 1440</p> <p>Main Stream 50 Hz: 20 fps (2560 × 1440) 25 fps (1920 × 1080, 1280 × 720) 60 Hz: 20 fps (2560 × 1440) 30 fps (1920 × 1080, 1280 × 720)</p> <p>Sub-Stream</p>

TECHNICAL SPECIFICATION

	<p>50 Hz: 25 fps (640 × 480, 640 × 360) 60 Hz: 30 fps (640 × 480, 640 × 360) Video Compression Main stream: H.265/H.264/H.265+/H.264+ Sub-stream: H.265/H.264/MJPEG Video Bit Rate 32 Kbps to 8 Mbps H.264 Type Baseline Profile/Main Profile/High Profile H.265 Type Main Profile H.264+ Main stream supports H.265+ Main stream supports Region of Interest (ROI) 1 fixed region for main stream</p> <p>Network Protocols TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour, IPv4, UDP, SSL/TLS Simultaneous Live View Up to 6 channels API Open Network Video Interface, ISAPI User/Host Up to 32 users. 3 levels: administrator, operator and user Client iVMS-4200, Hik-Connect Web Browser Plug-in required live view: IE 10+ Plug-in free live view: Chrome 57.0+, Firefox 52.0+ Local service: Chrome 57.0+, Firefox 52.0+</p> <p>Image Image Settings Saturation, brightness, contrast, sharpness, AGC, white balance adjustable by client software or web browser Day/Night Switch Auto, Schedule, Day, Night Image Enhancement BLC, 3D DNR</p> <p>Interface Ethernet Interface 1 RJ45 10 M/100 M self-adaptive Ethernet port</p> <p>Event Basic Event Motion detection, video tampering alarm, exception</p> <p>General Linkage Method Upload to FTP, notify surveillance center, send email Camera Material Aluminum alloy body Camera Dimension \varnothing 111 mm × 82.4 mm (\varnothing 4.4" × 3.2") Package Dimension 134 mm × 134 mm × 108 mm (5.3" × 5.3" × 4.3") Camera Weight Approx. 360 g (0.8 lb.) With Package Weight Approx. 560 g (1.2 lb.) Storage Conditions -30 °C to 60 °C (-22 °F to 140 °F). Humidity: 95% or less (non-condensing)</p> <p>Startup and Operating Conditions -30 °C to 60 °C (-22 °F to 140 °F). Humidity: 95% or less (non-condensing)</p> <p>Web Client Language English, Ukrainian</p> <p>General Function Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter</p> <p>Firmware Version V5.5.120</p>
--	--

TECHNICAL SPECIFICATION

	<p>Power Consumption and Current 12 VDC, 0.4 A, max. 5 W PoE: (802.3af, 36 V to 57 V), 0.2 A to 0.15 A, max. 6.5 W Power Supply 12 VDC ± 25% PoE: 802.3af, Class 3 Power Interface Ø 5.5 mm coaxial power plug Approval EMC FCC SDoC (47 CFR Part 15, Subpart B); CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 50130-4: 2011 +A1: 2014); RCM (AS/NZS CISPR 32: 2015); IC VoC (ICES-003: Issue 6, 2016); KC (KN 32: 2015, KN 35: 2015) Safety UL (UL 60950-1); CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013, IEC 62368-1:2014); CE-LVD (EN 60950-1:2005 + Am 1:2009 + Am 2:2013, IEC 62368-1:2014); BIS (IS 13252(Part 1):2010+A1:2013+A2:2015) Environment CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006) Protection IP67 (IEC 60529-2013), IK10 (IEC 62262:2002)</p>
<p>32 INCHES MONITOR</p>	<p>1920x1080p resolution Input: HDMI (VGA and DVI is a +) Frameless Design is a +</p>
<p>HDMI CABLES, MOUSE, BRACKET</p>	<p>MUST BE COMPATIBLE TO THE MONITOR</p>